

White gloss monomeric vinyl featuring a permanent clear adhesive. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

IP 2528

IP 2528 is a monomeric vinyl, incorporating a B1 fire rating, that has been specifically designed for printing with all solvent and UV inks. It can only be used on flat surfaces and is intended for indoor and short-term outdoor applications. IP 2528 features a strong, PE-coated, backing paper, which offers excellent lay flat properties. The product must not be wet applied - i.e. dry application only. Laminate: IP 2820-101, IP 2820-200 or IP 2830-200 (for trade shows, exhibitions, etc).

Specifications	
DESCRIPTION	Monomeric vinyl
COLOUR	White gloss
FACE FILM THICKNESS	80 μ
ADHESIVE	Acrylic permanent
ADHESIVE STRENGTH	16N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m ²
TEMPERATURE RANGE	-40°C to +80°C
DURABILITY (UNPRINTED)	Up to 3 years
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity

© June 2010 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.